

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Roberts 2077 Premium Carpet Tile Adhesive
Roberts MSDS Code # 2077C
PRODUCT USES: Pressure sensitive adhesive for installing carpet tiles

W.H.M.I.S. CLASSIFICATION: NON-CONTROLLED
V.O.C. CONTENT: 0 calculated

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: ROBERTS COMPANY CANADA LTD.
ADDRESS: 2070 Steeles Ave. Bramalea, Ontario L6T 1A7
24 HOUR (CANUTEC) PHONE: (613) 996-6666
DATE REVISED: December 01/06

NAME OF PREPARER: Technical Dept.
INFORMATION PHONE: (905) 791-4444
SOURCES USED: Raw material supplier M.S.D.S.

SECTION II - HAZARDOUS INGREDIENTS INFORMATION

COMPONENT	APPROX. %	UN#	CAS#	LD50	LC50
NO REPORTABLE INGREDIENTS COMPOUNDED ACRYLIC EMULSIONS					

SECTION III - PHYSICAL DATA

BOILING POINT: 100° C FREEZING POINT: N/A
VAPOUR DENSITY (AIR=1): Of water
VAPOUR PRESSURE (MM OF MERCURY): Of water.
SOLUBILITY IN WATER: Completely miscible
APPEARANCE AND ODOUR: White, medium syrup, sweet pleasant odour.

SPECIFIC GRAVITY (H2O=1): 1.03 pH: 4.5 - 5.5
EVAPORATION RATE (BUTYL ACETATE=1): As for water
EVAPORATION RATE (ETHYL ACETATE=1): As for water
PERCENT VOLATILE: 49
ODOUR THRESHOLD (PPM): Not available

SECTION IV - FIRE AND EXPLOSION DATA

FLASHPOINT (specify method): > 148°C
FLAMMABLE LIMITS (% BY VOLUME):
FIRE EXTINGUISHING MEDIA:
SPECIAL FIRE-FIGHTING PROCEDURES: Self-contained breathing apparatus should be worn for fires involving this product.
UNUSUAL FIRE AND EXPLOSION HAZARDS: None

METHOD USED:
LOWER: N/A UPPER: N/A
AUTO IGNITION TEMP: N/A

IMPACT SENSITIVITY: Insensitive
SENSITIVITY TO STATIC DISCHARGE: Insensitive
TDG FLAMMABILITY CLASSIFICATION: Not regulated.

SECTION V - REACTIVITY DATA

STABILITY: Stable
INCOMPATIBILITY (Materials to avoid): ND
HAZARDOUS DECOMPOSITION PRODUCTS: May be generated if product engulfed in fire.
HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: Excessive Heat, Freezing.
CONDITIONS TO AVOID: None

SECTION VI - TOXICOLOGICAL PROPERTIES

ENTRY ROUTE TABLE

SKIN CONTACT	X	SKIN ABSORPTION	EYE CONTACT	X	INHALATION ACUTE	INHALATION CHRONIC	INGESTION	X
--------------	---	-----------------	-------------	---	------------------	--------------------	-----------	---

EFFECTS OF ACUTE EXPOSURE TO MATERIAL: Eye contact may cause irritation. Ingestion may cause adverse health effects.

EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: Prolonged skin contact may cause irritation.

LD50 (SPECIFY SPECIES & ROUTE):	LC50 (SPECIFY SPECIES):	EXPOSURE LIMIT:	IRRITANCY:
Not available	Not available	Not available	May irritate eyes and skin
SENSITIZING CAPACITY:	CARCINOGENICITY:	REPRODUCTIVITY EFFECTS:	SYNERGISTIC MATERIALS:
None	None	None known	None known

SECTION VII - PREVENTATIVE MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE): No protection from vapours required. Dusk mask should be worn when spraying.
VENTILATION: General dilution ventilation.
PROTECTIVE GLOVES: Advisable (waterproof) EYE PROTECTION: Goggles
OTHER PROTECTIVE EQUIPMENT: None required.
SPILL PROCEDURES: Contain and collect with absorbent material. Wash area with water to remove residue. Prevent from entering sewers or waterways. Spilled material may cause slippery conditions. Promptly report significant spills to appropriate authorities. Consult local regulations.
WASTE DISPOSAL METHOD: Should be destroyed by dilution and liquid incineration at an approved facility. Dried material only may be landfilled. Consult local regulations.
STORAGE & HANDLING PRECAUTIONS: Store in ventilated space, out of direct sunlight, as close to 70°F as possible.
OTHER PRECAUTIONS: Keep containers tightly closed when not in use. Keep out of reach of children.

SECTION VIII - FIRST AID MEASURES

EYES: Flood with large quantities of water for 15 minutes. Consult physician.
SKIN: Wash with soap and water. Remove dried adhesive by gently swabbing with alcohol or other mild solvent.
INGESTION: Drink plenty of water. Do not induce vomiting. Consult a physician immediately.