

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Roberts 2990 Multi-Purpose Contract Adhesive
 Roberts MSDS Code # 2990C
 PRODUCT USES: For installing a wide variety of floorcovering materials

W.H.M.I.S. CLASSIFICATION: NON-CONTROLLED

V.O.C. CONTENT: 0 calculated

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: ROBERTS COMPANY CANADA LTD.
 ADDRESS: 2070 Steeles Ave. Bramalea, Ontario L6T 1A7
 24 HOUR (CANUTEC) PHONE: (613) 996-6666
 DATE REVISED: December 01/06

NAME OF PREPARER: Technical Dept.
 INFORMATION PHONE: (905) 791-4444
 SOURCES USED: Raw material supplier M.S.D.S., US M.S.D.S.

SECTION II - HAZARDOUS INGREDIENTS INFORMATION

COMPONENT	APPROX. %	UN#	CAS#	LD50	LC50
NO REPORTABLE INGREDIENTS					

SECTION III - PHYSICAL DATA

BOILING POINT: 100° C FREEZING POINT: N/A
 VAPOUR DENSITY (AIR=1): Heavier than air
 VAPOUR PRESSURE (MM OF MERCURY): As for water.
 SOLUBILITY IN WATER: Miscible
 APPEARANCE AND ODOUR: Beige, soft buttery paste, very mild resinous odour.

SPECIFIC GRAVITY (H2O=1): 1.2 pH: 9 - 10
 EVAPORATION RATE (BUTYL ACETATE=1): Slower
 EVAPORATION RATE (ETHYL ACETATE=1): Slower
 PERCENT VOLATILE: 50 - 54
 ODOUR THRESHOLD (PPM): Not available

SECTION IV - FIRE AND EXPLOSION DATA

FLASHPOINT (specify method): None
 FLAMMABLE LIMITS (% BY VOLUME):
 FIRE EXTINGUISHING MEDIA: Foam, CO2, Dry Chemical
 SPECIAL FIRE-FIGHTING PROCEDURES: Self-contained breathing apparatus should be worn for fires involving this product.
 UNUSUAL FIRE AND EXPLOSION HAZARDS: None

METHOD USED:
 LOWER: N/A UPPER: N/A
 AUTO IGNITION TEMP: N/A
 IMPACT SENSITIVITY: Insensitive
 SENSITIVITY TO STATIC DISCHARGE: Insensitive
 TDG FLAMMABILITY CLASSIFICATION: Not regulated.

SECTION V - REACTIVITY DATA

STABILITY: Stable
 INCOMPATIBILITY (Materials to avoid): Strong oxidizers and caustics
 HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2, and Hydrocarbons upon combustion.
 HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: Excessive Heat
 CONDITIONS TO AVOID: None

SECTION VI - TOXICOLOGICAL PROPERTIES

ENTRY ROUTE TABLE

SKIN CONTACT	SKIN ABSORPTION	EYE CONTACT	INHALATION ACUTE	INHALATION CHRONIC	INGESTION

EFFECTS OF ACUTE EXPOSURE TO MATERIAL: Product may irritate eyes and skin. Ingestion causes vomiting, diarrhea, depressed respiration.
 EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: Skin chapping.

LD50 (SPECIFY SPECIES & ROUTE):	LC50 (SPECIFY SPECIES):	EXPOSURE LIMIT:	IRRITANCY:
Not available	Not available	Not available	None
SENSITIZING CAPACITY:	CARCINOGENICITY:	REPRODUCTIVITY EFFECTS:	SYNERGISTIC MATERIALS:
None	None	None	None known

SECTION VII - PREVENTATIVE MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE): None
 VENTILATION: None should be required.
 PROTECTIVE GLOVES: None
 OTHER PROTECTIVE EQUIPMENT: None required.
 SPILL PROCEDURES: Mechanically collect. Wash area with water. Prevent from entering sewers or waterways. Spilled material may cause slippery conditions. Promptly report significant spills to appropriate authorities. Consult local regulations.
 WASTE DISPOSAL METHOD: Destroy by incineration at an approved facility. Dried material only may be landfilled. Consult local regulations.
 STORAGE & HANDLING PRECAUTIONS: Keep containers from excessive heat and freezing. Keep out of reach of children.
 OTHER PRECAUTIONS: None.

EYE PROTECTION: Goggles

SECTION VIII - FIRST AID MEASURES

EYES: Flush with water for 20 minutes, holding eyelids open. Seek medical attention.
 SKIN: Wash with soap and water. Seek medical attention if irritation develops.
 INGESTION: Do not induce vomiting. If victim is conscious, give milk or water. Contact physician immediately.